



PERFORMER SUITE

SAP BW/4HANA Role – Create & Update Function Modules

VERSION 22.1

SETTINGS VARIANT SCE ROLE DOCU

COMMENT VARIANT SCE ROLE COMMENTS

RESPONSIBLE PERSON ALEXANDER DÜRRSTEIN

CREATION DATE 08.03.2022

Role Z_ROLE_PS_ADMIN_BW4, Client 001

Table of contents

1	Docu Performer General Settings	3
2	Comment: Z_ROLE_PS_ADMIN_BW4/001 - Role for Creating and Updating Function Modules Role in BW (PS)	3
2.1	Objective	3
3	General Information	3
4	Role menu	3
5	Authorization data	3
5.1	AAAB - Cross-application Authorization Objects	3
5.2	BC_A - Basis: Administration	4
5.3	BC_C - Basis - Development Environment	4

1 Docu Performer General Settings

Performer Suite Settings	
Settings Variant	SCE Role Docu
Comment Variant	SCE Role Comments
Word Template	20200623_EN_Performer_Suite_Scenario_Template.dotx

2 Comment: Z_ROLE_PS_ADMIN_BW4/001 - Role for Creating and Updating Function Modules Role in BW (PS)

2.1 Objective

The Performer Suite requires customer-specific Function Modules to use all functions (see [User Manual](#)). The authorizations for this role are required to create or update those Function Modules. Keep in mind, the role must also have the correct Function Modules and Function Group authorizations (depending on your prefix used).

3 General Information

System	A4H
Role	Z_ROLE_PS_ADMIN_BW4/001, Role for Creating and Updating Function Modules Role in BW (PS)
Derived from Role	-
Related Single Roles	-
Profile name	T-AH320009
Profile text	Profile for role Z_ROLE_PS_ADMIN_BW4
Status	Authorization profile is generated
Last changed by	ADUERRSTEIN
Last change (timestamp)	02/03/2022 17:04:21
Timestamp of documentation	08/03/2022 15:19:49

4 Role menu

The role has no menu.

5 Authorization data

5.1 AAAB - Cross-application Authorization Objects

 S_RFC - Authorization Check for RFC Access [T-AH32000900]

Authorizations field	Values
ACTVT	16 Execute
RFC_NAME	/<customer namespace, if used>/, AUTHORITY_CHECK, ENQUEUE_READ, RFC_FUNCTION_DELETE, RFC_GET_FUNCTION_INTERFACE, RFC_GET_NAMETAB, RFC_READ_REPORT, RFC_READ_TABLE, RFC1, RFCPING, RPY_INCLUDE_UPDATE, RS_FUNCTION_POOL_INSERT, RS_FUNCTIONMODULE_INSERT, SDTX, SEUF, SIFP, SIW RFC_REPOSITORY, SIW RFC_WRITE_TADIR, SUNI, SUSR, SYST, USER_NAME_GET, Y*, Z*
RFC_TYPE	FUGR, FUNC

 S_SIW_CFG - Authorization for projects in SIW [T-AH32000900]

Authorizations field	Values
ACTVT	02
CONFIG_ID	<DUMMY>

5.2 BC_A - Basis: Administration

 S_TABU_NAM - Table Access by Generic Standard Tools [T-AH32000900]

Authorizations field	Values
ACTVT	03
TABLE	CVERS, DEVACCESS, E070V, E071, FUPARAREF, INFO_FUNCT, PROGDIR, RSTRANSTEPODSV, SEOCCLASS, TADIR, TFDIR, TLIBG

5.3 BC_C - Basis - Development Environment

 S_ABPLNGVS - ABAP Language Version [T-AH32000900]

Authorizations field	Values
ABP_LNG_VS	' '
ACTVT	01

 S_DEVELOP - ABAP Workbench [T-AH32000900]

Authorizations field	Values
ACTVT	01, 02, 03, 07, 16 Execute
DEVCLASS	\$TMP, /<customer namespace, if used>/*, Y*, Z*
OBJNAME	/<customer namespace, if used>/*, Y*, Z*
OBJTYPE	FUGR, FUNC
P_GROUP	*